

TECHNICAL DATASHEET



Cloth Adhesive Tape

▶ Product Description

PE coated cloth tape with a rubber based adhesive
High quality general purpose for irregular surface, water
proof, bundling, vinyl repair and packaging
Hand tearable, excellent waterproof and abrasion resistance.


▶ TECHNICAL DATA

backing : PE coated cloth adhesive-base : Natural rubber

total thickness (mm) : 0.26 peel adhesion (kg/25mm) : 1.0 rewinding force (kg/50mm) : 2 tensile strength (kg/25mm) : 8 holding power ($25mm \times 25mm / 40^{\circ}$) : 20min ball tack (cm / ball no. 20) : 15 heat resistance ($^{\circ}$ C) : 40 : 5 ~ 35 application temperature storage life (20°C / 60%) : 6 months

The used test methods are based on acceptable specifications like PSTC or internal test methods which are required on request.

▶ PRODUCT DESIGN



REMARK:

All the technical data are average values. We advice to test the material required to ensure the suitability of intended application. The company reserves the right to improve products and change specifications which may alter performance.

KB ADHESIVES CO., LTD.

TEL: +82-2-905-7864 FAX: +82-2-905-7867 www.kbgroupkorea.com info@kbgroupkorea.com

Overseas division: Rm. 402, Nene Bldg., 16-1, Chang 4 Dong, Dobong-gu, Seoul, Korea Factory: 630, Janggye-ri, Hwaseong-myeon, Cheongyang-gun, Chungcheongnam-do, Korea

LIMITED WARRANTY STATEMENT:

Products are warranted to be free of defects in workmanship and material at time of shipment. KB Adhesives Korea Ltd. will replace or credit any material we determine to be defective. Before using, user shall determine the suitability of the product for itsintended use, and user assumes all risk and liability whatsoever in connection therewith.



