



Non Woven Double Sided Tape 25000LX

► Product Description

Strong fabric non woven, Easy removable and strong mounting power,
 Unique adhesive formulation, without residue after performance,
 Apply for wide range of materials (like plastic, metal...), Low and high service temperature ability

► Technical Data

Test standard	China GB	ASTM	FINAT	JIS
Tape Thickness(mm)	0.16			
Color	Opaque			
Adhesion Power	20N/25mm	20N/25mm	20N/25mm	20N/25mm
Initial Tack	13#(ball)	8cm	11N/25mm	13#(ball)
Holding Power	>100 hours	>100 hours	>100 hours	>100 hours

► Application

Bonding and sealing components, parts of electronic equipment and home appliance such as TV, air-conditioner, printer and copy machine, fax machine etc. It helps environmental recycling and it is removable without tearing and residue.



► Construction



Modified Solvent base Acrylic Adhesive
 Strong fabric non-woven g/m2
 Modified Solvent base Acrylic Adhesive
 PE paper release liner 115g/m2

► Temperature

Application (Minimum): 10 °C
 Service (long term): -20 °C to 120 °C
 Short term: 180 °C

► Standard Size

	Tape width	Usable width	Length
Jumbo rolls	1220mm	1200mm	500, 700, 1000M
Log rolls	1220mm	1200mm	50, 100M

► Surface Preparation

It is essential, as with all pressure sensitive tapes, that the surface to which the tape is applied be clean, dry and free of grease and oil

► Storage and Shelf Life

The shelf life of the products is one years when stored at 18-25 °C, 30-70% relative humidity and out of direct sunlight, in good packaging.