



Double Sided Tissue Tape 221

► Product Description

Soft adhesion and high initial tack, non-yellow changing, good season resistant. Especially, lamination to foam material, cotton fabric and cloth.

► Technical Data

Test standard	China GB	ASTM	FINAT	JIS
Tape Thickness(mm)	0.14			
Color	Translucent			
Adhesion Power	15N/25mm	15N/25mm	15N/25mm	15N/25mm
Initial Tack	15#(ball)	6cm	13N/25mm	15#(ball)
Holding Power	12 hours	12 hours	12 hours	12 hours

► Application

Bonding to polyethylene and polypropylene and many other plastics, paper. Mounting indoor sign, plaque, trim. Laminating different kinds of foam materials (like EVA, PE, PU foam) in household electric appliance, auto car and construction, also for cotton fabric, cloth lamination.



► Construction



Solvent base acrylic adhesive
Tissue 14g/m²
Solvent base acrylic adhesive
PE paper release liner 105g/m²

► Temperature

Application (Minimum): 10°C
Service (long term): -20°C to 60°C
Short term: 80°C

► Standard Size

	Tape width	Usable width	Length
Jumbo rolls	1040, 1260mm	1020, 1240mm	500, 700, 1000M
Log rolls	1040, 1260mm	1020, 1240mm	50, 100M

► Surface Preparation

It is essential, as with all pressure sensitive tapes, that the surface to which the tape is applied be clean, dry and free of grease and oil

► Storage and Shelf Life

The shelf life of the products is one year when stored at 18-25°C, 30-70% relative humidity and out of direct sunlight, in good packaging.