



Bondler®

Double Sided Tissue Tape 2501F

► Product Description

501F is a high performance tissue carrier double-sided tape with excellent adhesion, good holding power, excellent temperature resistance and repulsion resistance. Design application on Rice-Cooker, Refrigerator, Temperature Controller Heater for heating component lamination.

► Technical Data

Test standard	China GB	ASTM	FINAT	JIS
Tape Thickness(mm)	0.14			
Color	Translucent			
Adhesion Power	15N/25mm	15N/25mm	15N/25mm	15N/25mm
Initial Tack	13#(ball)	.	.	13#(ball)
Holding Power	>100 hours	>100 hours	>100 hours	>100 hours

► Construction



Modified solvent base acrylic adhesive
 Tissue 14g/m²
 Modified solvent base acrylic adhesive
 PE paper release liner 110g/m²



► Temperature

Service (long term): -20°C to 150°C
 Short term: 200°C

► Standard Size

	Tape width	Usable width	Length
Jumbo rolls	1040, 1260mm	1020, 1240mm	500, 700, 1000M
Log rolls	1040, 1260mm	1020, 1240mm	50, 100M

► Surface Preparation

It is essential, as with all pressure sensitive tapes, that the surface to which the tape is applied be clean, dry and free of grease and oil

► Storage and Shelf Life

The shelf life of the products is one years when stored at 18-25°C, 30-70% relative humidity and out of direct sunlight, in good packaging.